

タンデム・ミキサー 技術データ

Model number	Unit	IM320E	IM550E	IM550ET	IM1000ET
Chamber volume	l, approx.	332	565	620	980
Useful volume at fill factor 0.75	l, approx.	232	396	-	-
Batch weight at specific gravity 1.15 kg/l	kg, approx.	279	-	-	-
Standard rotor speed	rpm	5-50	5-50	5-50	5-50
Related motor power	kW	140-1400	256-2300	80-800	150-1500
Ram pressure on compound	N/cm ² , approx.	50	50	-	-
Useful volume of the feeding hopper up to the feed door shaft	l, approx.	730	1184	-	-
Useful volume of the feeding hopper up to feed opening	l, approx.	915	1184	-	-
Dimension of feed hopper	Length in mm	1016	1200	1200	1350
	Width in mm	500	610	610	710
Dimensions of drop door	Length in mm	1016	1200	1200	1350
	Width in mm	520	610	610	710
Space requirements for mixer and gearbox, excluding motor	Length in mm, approx.	6600	6200	6200	7700
	Width in mm, approx.	4650	5200	5200	5200
	Height in mm, approx.	6500	7000	3000	3500
Weight of internal mixer, excluding drive	kg, approx.	41000	56000	42000	61000